

Narendra



**LEFT
TO
RIGHT
C-FRAME
PRESS**

SERIES NSR



TECHNICAL SPECIFICATIONS

MODEL		NSR-35	NSR-45	NSR-63	NSR-110	NSR-160	NSR-200	NSR-250
CAPACITY	TON	35	45	63	110	160	200	250
STROKE LENGTH - FIXED	MM	63	80	100	125	160	200	200
STROKE PER MINUTE	SPM	60	55	50	45	40	35	30
DIE HEIGHT	MM	250	280	300	350	400	400	450
SLIDE ADJUSTMENT	MM	50	63	63	80	100	100	100
SLIDE AREA LR X FB	MM	355X250	400X250	500X400	600X500	710X600	750X650	850X700
SHANK HOLE DIAMETER	MM	Ø50	Ø50	Ø50	Ø50	Ø65	Ø65	Ø65
BOLSTER AREA LR X FB	MM	630X400	710X450	825X500	1000X600	1100X710	1200X750	1350X800
BOLSTER THICKNESS	MM	80	85	110	120	140	160	180
HEIGHT OF BLOSTER FROM FLOOR	MM	800	800	800	900	900	950	950
MAIN MOTOR	HP X P	3	5	7.5X4	10X4	15X4	20X4	25X4
SLIDE ADJUSTMENT MOTOR	HP X P	----	----	----	0.5X4	1X4	1X4	1.5
CUSHION CAPACITY	TON	----	----	6.3	8	10	14	14
CUSHION STROKE LENGTH	MM	----	----	90	90	100	110	110
PRESSURE PAD AREA	MM	----	----	410X260	480X300	540X340	640X440	640X440
ACCURACY	JIS GRADE -1							

Manufactured and Marketed by:

NARENDRA PRESS TECH PVT. LTD.

P.P. 26, Lane no. 10, Behind Police Station,

Anand Parbat Industrial Estate, New Delhi-110 005, (INDIA)

Ph. : + 91-11-28761468, +91-11-28761467, Fax : +91-11-28761576 .

UNIT - 2

PLOT NO. 65, SECTOR 3, IMT MANESAR, GURGAON, HARYANA (INDIA).

TELEFAX.: 0124 2291354

E-mail : sales@narendrapresstech.com Website : www.narendrapresstech.com

We reserve the right to change, design and modify specification at the discretion of our engineering department