

Narendra

**STRAIGHT
SIDED
TWO POINT
PRESS**



SERIES NSE



TECHNICAL SPECIFICATIONS

MODEL		NSE-63	NSE-100	NSE-125	NSE-160	NSE-200
CAPACITY	TON	63	100	125	160	200
RATING POINT	MM	4	5	5	6	6
BOLSTER AREA LR X FB	MM	1000X500	1100X600	1200X600	1600X1200	1700X1200
SLIDE AREA LR X FB	MM	1000X500	1100X600	1200X600	1500X1000	1600X1000
FIXED STROKE	MM	100	125	125	160	200
DIE HEIGHT	MM	300	350	370	400	400
SLIDE ADJUSTMENT	MM	70	80	90	110	125
BLOSTER THICKNESS	MM	120	140	140	140	160
WINDOW OPENING	MM	300X400	300X400	300X400	450X400	450X400
FLOOR TO TOP OF BLOSTER	MM	900	900	900	900	1000
AIR PRESSURE	kg/cm ²	5	5	5	5	5
SPEED	SPM	60	50	45	40	35
MAIN MOTOR	HP	7.5	10	15	15	20
SLIDE ADJUSTMENT MOTOR	HP	1	1.1	1.1	1.5	1.5

Manufactured and Marketed by:

NARENDRA PRESS TECH PVT. LTD.

P.P. 26, Lane no. 10, Behind Police Station,

Anand Parbat Industrial Estate, New Delhi-110 005, (INDIA)

Ph. : + 91-11-28761468, +91-11-28761467, Fax : +91-11-28761576 .

UNIT - 2

PLOT NO. 65, SECTOR 3, IMT MANESAR, GURGAON, HARYANA (INDIA).

TELEFAX.: 0124 2291354

E-mail : sales@narendrapresstech.com Website : www.narendrapresstech.com

We reserve the right to change, design and modify specification at the discretion of our engineering department